

Sectional Directional Control Valve RS 280



Key valve features

RS 280 is a sectional valve designed for max. operating pressures up to 275 bar and max. pump flows up to 120 l/min.

It is available with 1 to 10 working sections per valve assembly.

RS 280 is designed with an open center for fixed displacement pumps.

The valve can be operated manually, by pneumatic, electro-pneumatic or hydraulic remote control.

The valve offers excellent operating characteristics because of the specially designed spools for different applications.

Low and uniform spool forces are the result of careful balancing of the flow forces.

Applications

Typical applications for RS 280 are cranes, tippers, truck loaders, backhoe loaders and wheel loaders.

Further RS 280 properties and possibilities

- Many varieties of spools and spool controls make the valve suitable for a wide range of applications
- Each section can be provided with a pressure relief valve, an anti-cavitation valve or a combination of these
- Possibility of high pressure carry-over
- With combination of an intermediate section there is the opportunity to realize different system alternatives, for example dual pump circuits, built in one compact valve

Technical data

Pressures / Flow

Max. operating pressure per port:

P1, P2, PL1, A, B: 275 bar

T1, T2, T3, T4: 20 bar

Max. permissible flow either on port P1, P2 or PL1: 120 l/min

Fluid temperature range: -15 °C up to +80 °C

Further data

Spool stroke:

Nominal: +/- 8 mm

4:th position: + 15 mm

Spool control force spool control 9:

Neutral position: 110 N

Max. spool stroke: 140 N

Detent in: > 425 N

Detent out: < 225

Permissible contamination level: Equal or better than 20/18/14 as per ISO 4406


Viscosity range: 10 – 400 mm²/s (cst)
Higher viscosity allowed at start up

Leakage A, B → T at 100 bar, 32 cst and 40 °C: ≤ 18 cc/min


Pressure fluid: Mineral oil and synthetic oil based on mineral oil HL, HLP according to din 51524

Higher values are possible, depending on application. For applications with demands that exceed stated data above, please contact us for consideration.

MTTFd value after consultation with HYDAC.




General overview




Pressure drop


Oil temperature / viscosity for all graphs: +40 °C / 32 cSt



Pressure drop P – T




Pressure drop P – A/B



Pressure drop A/B – T

Dimensions and Weight



Weight

Inlet section	4.4 kg
Outlet section	5.0 kg
Working section	5.0 kg
Intermediate section	4.4 kg

No. of sections	L [mm]	LF [mm]	LK [mm]
1	153	134	97
2	200	181	144
3	247	228	191
4	294	275	238
5	341	322	285
6	388	369	332
7	435	416	379
8	482	463	426
9	529	510	473
10	576	557	520




Type	LA [mm]	Type	LB [mm]
910	40.5	M1	42
10	87	M2	15
11	87	M3	52
13	87	3W	92
14	87	4W	102
L81-83	105	HPD1B	72
P	103		
EP	134		
HPD1A	72		
HPD405	107.5		

Main relief valves

Main relief valve TBD201

The TBD201 is a differential area, direct acting relief valve, for the main circuit. It is adjustable and sealable.




- Setting range:
35 – 275 bar
(3.5 – 27.5 MPa)
- Setting range step: 5 bar



Main relief valve TBS400

Pilot operated relief valve for the intermediate section. It is adjustable and sealable.

- Setting range: 35 – 275 bar
(3.5 – 27.5 MPa)
- Setting range step: 5 bar






Service port valves

Port relief valve TBD202

The TBD202 is a differential area, direct acting relief valve for the secondary circuit.

- Setting range:
35 – 275 bar
(3.5 – 27.5 MPa)
- Setting range step: 5 bar






Port relief and anticavitation valve TBSD202

Characteristics: See particulars of the port relief valve and the anticavitation valve.

The TBSD202 is a differential area, direct acting relief and anticavitation valve, for the secondary circuit.




It is adjustable and sealable.

- Setting range: 35 – 275 bar
(3.5 – 27.5 MPa)
- Setting range step: 5 bar








Anticavitation valve SB250

The anticavitation valve service to ensure that, in the event of a lower pressure in the cylinder port than in the tank, oil can be drawn from the system oil tank to the consumer.



Spool controls – A-side

Spool control 9 9 Spring centered	
Spool control 10 Detents at positions 1, 2 and 3	
Spool control 11 Spring centering with detent at position 4	
Spool control 13 Spring centering with detent at position 2	
Spool control 14 Spring centering with detent at position 3	
Spool control P Pneumatic*	
Spool control EP Electro / pneumatic on / off**	
Spool control HPD1 Hydr. proportional Pilot pressure: 6 – 16 bar Max. pilot pressure: 25 bar***	
Spool control HPD405 Hydr. proportional spool control with float in 4th position***	
Spool control L81 External hydraulic kick-out from inserted spool***	
Spool control L82 External hydraulic kick-out from extended spool***	
Spool control L83 External hydraulic kick-out from inserted and extended spool***	

* Connection G 1/8" BSP


*** Connection G 1/4" BSP

** Power consumption	4.8 W
Rated voltage	24 V
Max voltage variation	+/- 10 %
Duty factor	100 %
Connection	according to EN175301-803/B
Protection class	IP65

Spool controls – B-side

Bracket M1 Bracket for 3-position spool	3W Cap for 3-position spool controlled by cable
Bracket M2 Bracket for 3-position spool, without ear	4W Cap for 4-position spool controlled by cable
Bracket M3 Bracket for 4-position spool	

Spools



Spools for general use

Function

Code

	Double acting spool	1X
	Single acting spool P – B	2X
	Double acting spool with 4th pos. for float	3X
	Motor spool	4X
	Motor spool A – T	4XA
	Motor spool B – T	4XB

The RS 280 spools are available in variety of flows and styles to accommodate most design requirements. Since the development of spools is a continuous process and all available spools are not described in this data sheet, contact Hydac for advice on choosing spools in order to optimize your valve configuration.

Generally the spools are divided in 6 different flow ranges. The letter indicating flow ranges is replaced by X.


D = 60 l/min, F = 70 l/min, H = 80 l/min, G = 90 l/min, K = 120 l/min.

In the table only the accessibility of different functions are shown.


High pressure carry-over

High pressure carry-over plug PS28

Plug PS28, mounted in S1 allows a high pressure carry-over function.




System alternatives with intermediate section



The intermediate section allows a number of different internal and external system alternatives.


Existing valve equipped with the intermediate section can easily be altered to other system configurations without dismantling the valve.



K1, Single circuit

Valve internally parallel coupled.


Main relief valve for the system can be positioned in the intermediate section.



K2, Single circuit

Valve internally tandem coupled, i. e. working sections upstream of the intermediate section with fully selected spools have complete priority as far as flow supply is concerned in relation to working sections downstream of the intermediate section.


A second main relief valve, positioned in the intermediate section, can be used to reduce the pressure to working sections downstream from the intermediate section.



K3, Dual circuit

The intermediate section divides the valve into two completely separated circuits. The tank gallery is common.

Multicircuit operation is possible according to the same pattern.



K5, Dual circuit

Tandem coupling between first and second circuit.

The first circuit is always solely supplied from the first pump.

The second circuit is always supplied from the second pump.

When the first circuit is inactive then the second circuit is supplied from both pumps.

Multicircuit operation is possible according to the same pattern.

Typical hydraulic circuit diagrams




Diagram 1: High pressure carry-over

In parallel connection the same pump is connected to two or more valves.
The function is the same as if the pump was connected to one large valve.






Diagram 2: Two pump circuit with intermediate section (K3)





Note

The information in this brochure relates to the operating conditions and applications described.

For applications or operating conditions not described, please contact the relevant technical department.
Subject to technical modifications.



Nordhydraulic

HYDAC INTERNATIONAL

**Head Office
HYDAC INTERNATIONAL
GMBH**

Industriegebiet
66380 Sulzbach/Saar
Germany

Tel.: +49 6897 509-01
Fax: +49 6897 509-577

E-mail: mobilevalves@hydac.com
Internet: www.hydac.com