

AS9100 & ISO 9001 Certified

Compact Solutions for 2 Speed Applications

Contained in a small efficient package, the Lynch 2 Speed Valves are built to go from full speed to a slow controlled motion by simply energizing the solenoid.

Available in aluminum or ductile iron, with flow rates up to 120 GPM.

Series 1-3 Inline Models



Inline Model with SAE
16 Ports and Pressure
Compensated Flow
Control.

Line Mounted Bodies available:

- SAE
- BSPP
- Metric
- NPT
- BSPT
- SAE Flange
- Normally open or closed solenoid options.
- Rated up to 60 GPM and 5000 PSI
- Coil voltages from 12 VDC to 230 VAC.
- Flow control options include needle valve, flow control with reverse free flow check, or pressure compensated flow control.
- All valves are available with adjustment screw, hand knob, or calibrated hand knob.
- Seals are Buna "N" or Viton ®.

D03, D05, D07 & D08 Sandwich Modules



D03 Sandwich Module
Meter in "P" with Needle
Valve.

Circuits available:

- Meter In "P" and Out "T"
- Meter In "A" and Out "A"
- Meter In "B" and Out "B"

Contact Your Equipment Dealer For Further Details

Contact Us For More Information

Local & International

Tel: +1 (905) 363-2400

Fax: +1 (905) 363-1191

Toll Free

Tel: 1 (888) 626-4365

Fax: 1 (800) 263-5807

Online

www.Lynch.ca

sales@lynch.ca

Address

1799 Argentia Road

Mississauga, Ontario L5N 3A2